Termosoffiatore

HG5030K

1.600 W • 300 / 500 l/min • 350 / 500 °C

Termosoffiatore 1,600W 500° - 2 Vel

Termosoffiatore base da 1,600W dotato di impugnatura ergonomica per un uso impegnativo in diverse applicazioni, compresa la sverniciatura. Due impostazioni di calore e di flusso d'aria: velocità 1 - 350° per formatura, velocità 2 - 500° per termoretrazione, rimozione pitture, saldatura e operazioni di induritura. Fornisce fino a 500L/min a 500°C. Accessori in dotazione: 4 ugelli, valigetta.

SPECIFICHE TECNICHE

Max Potenza erogata	1600 W
Portata massima	300 / 500 L/min
Range temperatura	350 - 500 °
Interruttore di sicurezza termica	✓
Peso senza cavo (Procedura EPTA 01/2003)	0,56 kg
Dimensioni prodotto	233 x 80 x 208 mm
Cavo di alimentazione	2,0 m

Codice EAN 0088381857321

Collegamento alla pagina del prodotto - www.makita.it

PRODOTTI CORRELATI

ACCESSORI IN DOTAZIONE

PR00000028
Glass Protection Nozzle 45mm

PR00000029
Wide Slot Nozzle, 50 mm

PR00000030
Reflection Nozzle, 40 mm

PR00000031
Reduction Nozzle, 20 mm

ACCESSORI OPTIONAL

PR00000029
Wide Slot Nozzle, 50 mm

PR00000030
Reflection Nozzle, 40 mm

PR00000031
Reduction Nozzle, 20 mm

PR00000032
Overlap Welding Nozzle, 24 mm

PR00000033
Reflection Nozzle, 5 mm

PR00000034
Welding Nozzle, 65 mm

PR00000035
Pressure roller

PR00000036
Welding Rods, ABS, 5 x 230 mm, 10

PR00000037
Welding Rod, HDPE, 10 pcs

PR00000038
Welding Rod, PP, 10 pcs

PR00000039
Speed Welding Nozzle

PR00000041
Scraper Set

PR00000042
Contour Scraper