



## SAFETY

4 06 10 / 1 Anthracite

**Scarpa omologata da lavoro per uso professionale.**  
**Indicata per il soccorso in ambienti scoscesi e terreni impervi. Utilizzato dal personale di Soccorso 118, Croce Rossa, lavori agricoli, forestali e per l'industria.**  
 Pelle camoscio idrorepellente, altamente traspirante e molto resistente. Membrana traspirabile idrorepellente in PTFE con costruzione a bootie, tessuto in rete mesh traspirante a contatto con il piede. Suoletta antiperforazione in tessuto che non limita la flessibilità della calzatura. Suola con ottima rullata per un maggior comfort in camminata, mescola antistatica, nitrilica e antiolio, resistente agli idrocarburi e resistente al calore per contatto con zeppa in microporosa ammortizzante e isolante. Puntale incorporato alla calzatura stessa senza possibilità di essere rimosso e resistente alla corrosione a norma EN 12568:2010.

Approved work boot for professional use. Indicated for the relief rugged environments and difficult terrain. Used by the rescue personnel 118, Red Cross, agricultural works, forestry and industry.

Water repellent, highly breathable and very durable suede leather. Water-repellent, breathable PTFE membrane with bootie construction, breathable mesh fabric in contact with the foot. Perforation-resistant insole with fabric that improves the shoe flexibility. Sole specific shaped for a natural walk movement. Sole properties: antistatic, anti-oil and nitrile, hydrocarbons and heat resistant PU wedge, shock-absorbing and insulating. Unremovable shoe embedded toe cap, corrosion resistant in accordance with EN 12568:2010 standard.



BANDA DI COLORE GIALLO AD ALTA VISIBILITÀ  
 HIGHLY VISIBLE YELLOW COLOR BAND



PUNTALE IN ACCIAIO RESISTENTE A 200 JOULE  
 STEEL TOE CAP RESISTANT TO 200 JOULES



SOLETTA CON TESSUTO MULTISTRATO ANTIPIERFORAZIONE  
 MULTILAYER ANTI-PERFORATION INSOLE

CERTIFICATION	EN ISO 20345:2011 EN ISO 20344:2011 S3 - HI - CI - WR - FO - SRC II category PPE - I class
UPPER	Suede leather 1,8 mm
LINING	Mesh + 3 layers waterproof eVent® membrane
FOOTBED	Fitwell Air Move
INSOLE	Anti-perforation fabric that does not limit the flexibility of the shoe and antistatic processing
TOE CAP	200 joule resistant steel
SOLE	Vibram® Jankuat antistatic + EVA double density
SIZE	36 - 48 EUR
WEIGHT	690 gr ½ pair, size 42

